

TOP ORIENTATION VIEW

A	
$ \begin{array}{c} $	
4 1/2"ø — 9"	
(D) <u>DIMENSIONAL</u>	<u>VIEW</u>

NOZZLE SCHEDULE									
MARK	SIZE	SPEC	NOZ. TYPE	FUNCTION					
A	1/4"	6000#	CPLG	VENT					
В	3/4"	6000#	CPLG	INLET					
C	3/4"	6000#	CPLG	OUTLET					
D	3/4"	6000#	CPLG	DRAIN					

NOTE: 1. DESIGNED, FABRICATED AND STAMPED IN ACCORDANCE WITH ASME CODE SECTION VIII, DIV. 1.

2. SEPARATORS AVAILABLE IN CARBON STEEL, 304 & 316 STAINLESS STEEL, OR OPTIONAL ALLOYS UPON REQUEST.

3. ALL DIMENSIONS ARE IN INCHES

4. WEIGHT (DRY) = 32 LBS.

		REVISION: <u>0</u>							
		NO. DE	SCRIPTION	BY DATE	NO.	DESCRIPT	10N		
CONSTR	UCTION	DIDION SEPARATOR COMPANY							
A.S.M.E. SECTIO		A DIMBONS							
A.S.M.E. (3) -01 .	STAMP REQUIRED	PH: (419) 483-	-2220	DIDION'S MI		WEB:	didionsepo		
		FX: (419) 483- DESCRIPTION		NOT BIGGE		• • • • • • • • • • • • • • • • •	il: dmech@did	ionsmech.com	
DECION CDE	OIFIGATIONS								
		FICATIONS MODEL#: DST75-NPT							
DES. PRESS.	500 PSIG	SALES DRAWING							
DES. TEMP.	650° F.	DRWN. JLD	DATE	: 10/18/16	ΑP	PR.	DATE:		
FULL VACUUM	YES	CHK.	DATE	:	AP	PR.	DATE:		
CORR. ALL.	1/16"	SCALE:		DRAWING NUMBER REV. SHE			SHEET		
HYDRO. TEST	650 PSIG	D.M. NO. DST75-NPT-SALES 0 NO. 1					NO1_		
STRESS REL.	NONE REQ'D	P.O. NO.		51/5-1	ו או	-SALES		0F1_	
RADIOGRAPH	NONE REQ'D					ION'S MECHANICAL. IT IS			
M.D.M.T	-20° F. @ 500 PSIG					st. Neither this drawi Nished to others nor I			
		OF ANY ARTICLE FABRICATED OR ASSEMBLED FROM THIS DRAWING WITHOUT CONSENT OF DIDION'S MECHANICAL.							